

# imagePROGRAF PRO-6000

## LARGE FORMAT PHOTOGRAPHIC AND ART PRINTING HAS NEVER BEEN SO IMPRESSIVE.

The 60-inch large format printer in a league of its own – with peerless print quality, productive output speeds and supreme reliability.



### KEY FEATURE

- Class-leading print quality for a 60-inch model, with LUCIA PRO 12-colour ink system
- Productive print speeds realized by the 1.28-inch-wide print head
- Efficient workflow enabled by dual-roll unit, offering continuous feeding and automatic paper take-up
- Space-saving compact and attractive body
- Simplified user operation thanks to 3.5-inch colour touch screen
- Newly developed multi-position basket allows for numerous configuration options
- Fast and easy printing of PDF and JPEG file formats directly from USB memory stick
- Quick and easy Wi-Fi connectivity
- Minimised maintenance and production interruptions from high-capacity “hot swap” ink tanks
- Reliable performance and guaranteed colour consistency across every unit

### PRODUCT RANGE



**Canon imagePROGRAF PRO-6000**



Canon imagePROGRAF PRO-4000



Canon imagePROGRAF PRO-2000



Canon imagePROGRAF PRO-1000

**Canon**

---

# TECHNICAL SPECIFICATIONS

# imagePROGRAF PRO-6000

## TECHNOLOGY

<b>Printer Type</b>	12 Colour 60"/1524mm
<b>Print Technology</b>	Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head)
<b>Print Resolution</b>	2,400 x 1200 dpi
<b>Number of Nozzles</b>	18,432 nozzles (1536 nozzles x 12 colour)
<b>Line Accuracy</b>	±0.1% or less
	User adjustments necessary. Printing environment and media must match those used for the adjustments.
	CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only
<b>Nozzle Pitch</b>	600 dpi x 2 includes Non-firing nozzle detection and compensation system
<b>Ink Droplet Size</b>	minimum 4 pl per colour
<b>Ink Capacity</b>	Sales Ink: 160ml/330ml/700ml Bundled Starter Ink: 330ml
<b>Ink Type</b>	Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey, Photo Grey, Red, Blue, Chroma Optimiser
<b>OS Compatibility</b>	Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2 Apple Macintosh: OSX 10.7.5 - 10.11
<b>Printer Languages</b>	SG Raster (Swift Graphic Raster), PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)
<b>Standard Interfaces</b>	USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB 2.0 Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b *Please refer to user manual how to activate/deactivate the wireless LAN

## MEMORY

<b>Standard memory</b>	3 GB
<b>Hard Drive</b>	320 GB

## PRINT TIME FOR A0 PAGE SIZE

<b>Media Type</b>	Print Mode:	Print Time
<b>Plain Paper</b>	Print Mode	Print Time
	Fast	1:37 min
	Standard	2:51 min
<b>Coated Paper</b>	Print Mode	Print Time
	Standard	2:51 min
	High Quality	5:36 min
<b>Glossy Photo Paper</b>	Print Mode	Print Time
	Standard	6:21 min
	High Quality	10:05 min

## MEDIA HANDLING

<b>Media Feed and Output</b>	Upper Roll Paper: One Roll, Front-loading, Front Output Lower Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever)
<b>Media Width</b>	Roll paper: 203.2 - 1524 mm Cut sheet: 203.2 - 1524 mm
<b>Media Thickness</b>	Roll/Cut: 0.07 - 0.8 mm
<b>Minimum Printable Length</b>	203.2 mm
<b>Maximum Printable Length</b>	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m
<b>Maximum Media Roll Diameter</b>	170 mm
<b>Media Core Size</b>	Internal diameter of roll core: 2 1/3"
<b>Margins Recommended area</b>	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

## Margins Printable area

Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm  
Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm  
Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm

## Media Feed Capacity

Roll Paper: Two rolls. Automatic switching is possible.  
Cut Sheet: 1 sheet

## Media Take-up roll unit

Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

## Borderless Printing Width (Roll Only)

515mm (JIS B2), 728mm (JIS B1), 1030mm (JIS B0), 594mm (ISO A1), 841mm (ISO A0), 10", 14", 17", 24", 36", 42", 44", 257mm (JIS B4)\*, 297mm (ISO A3)\*, 329mm (ISO A3+)\*, 420mm (ISO A2)\*, 8\*\*\*, 16\*\*\*, 30\*\*\*, 300mm\*

\*Some environmental conditions may not produce the desired result

## Maximum number of delivered prints

Standard position: 1 sheet  
Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)

## DIMENSIONS AND WEIGHT

### Physical Dimensions WxDxH (mm) and Weight (Kg)

1999 x 984 x 1168 mm (Basket Open)  
1999 x 766 x 1168 mm (Basket Closed)  
167 kg (including Roll Holder Set and Roll unit, excluding ink and print heads)

### Packaged Dimensions WxDxH (mm) and Weight (Kg)

Printer (Main unit with pallet): 2227 x 915 x 1022 mm  
210 kg  
Roll Unit: 2133 x 562 x 461 mm  
40 kg

## POWER AND OPERATING REQUIREMENTS

### Power Supply

AC 100-240V (50-60Hz)

### Power Consumption

Operation: 103 W or less  
Sleep mode: 3.6W or less  
Default setting for the time to enter the Sleep mode: Approx. 5 Minutes  
Power off: 0.3 W or less

### Operating Environment

Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)

### Acoustic Noise (Power/Pressure)

Operation: 50 dB (A) (Glossy paper, Print priority: Standard)  
Standby: 35 dB (A) or less  
Operation: 6.7 Bels or less (Glossy paper, Image, Print priority: Standard) (Measured on ISO 7779 standard)

## Regulations

Europe: CE mark, Russia: EAC,  
Other countries: CB certification

## Environment Certificates

International Energy Star Program (WW), RoHS

## WHAT'S INCLUDED

### What's in the Box?

Printer, Roll Unit, 1 x Print Head, 1 x Maintenance Cartridge, 3" Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard Environment Leaflet, User Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Printhead Alignment Sheet

## Software Included

imagePROGRAF PRO Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite  
Other software available as Download from Web.

## OPTIONS

### Optional Items

2/3" Roll Holder: RH2-45

## CONSUMABLES

### User Replaceable Items

Ink Tank: PFI-1100 (160ml), PFI-1300 (330ml), PFI-1700 (700ml)  
Print Head: PF-10  
Cutter Blade: CT-07  
Maintenance Cartridge: MC-30

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Crystal-fidelity



Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com  
English edition  
© Canon Europa N.V., 2017